



**GESS<sup>®</sup>**  
TECHNOLOGIES

GESStremeHD™

GESStHD™-NVR3220S

SKU # GESStHD-NVR3220S

## Main Features

- 32ch D1
- 32ch 720P
- 32ch 1080P(6M) Input
- 1080P HDMI Output
- P2P
- 3G
- Cloud Storage
- 2U



## Technical Specifications

SKU#		GESStHD-NVR3220S
Special function	P2P function	Using Device ID and password to login <a href="http://www.vssweb.net">www.vssweb.net</a> , realize remote monitoring, playback and control like IE Web login. No need any network, IP setting, easy for end user to use network function.
	Cloud Storage	Support Dropbox and Google Drive.
System	Operation System	Embedded LINUX
	Pentaplex function	Live monitoring, recording, playback, backup & remote access
	Control Mode	Front panel, USB mouse, IR remote control, Network
Video	IP Camera Input	32ch.(200Mbps)
	Decoding Capability	16ch.D1@30fps 13ch.720P@30fps 6ch.1080P@30fps
	Support Protocol	ONVIF, GESS Technologies
	Standard	PAL (625line, 50f/s) NTSC (525line, 60f/s)
	Output	1 CVBS, BNC (1.0Vp-p,75 ohms)
		1 HDMI, 1.3a,support 1920×1080 Resolution 1 VGA,1920×1080,1440×900,1280×1024,1024×768,800×600 Resolution
Audio	Output	1 BNC (2.0Vp-p,300 ohms)
	Two-way Talk	1ch. Standalone
Display	IP Resolution	Main stream:up to 5632x4224 Auxiliary stream:4CIF
	Resolution	5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
	Frame	1~30fps
	Tour Display	Support
	Privacy Masking	Four zones for privacy masking for each channel
Recording	Video Compression	H.264/MPEG 4 AVC,up to Main Profile 5.0
	Audio Compression	G.711A,G.726
	Image Encoding	Adjustable encoding quality, variable code stream/fixed code stream
	Dual Stream	Support
	Recording Mode	Manual, auto, motion detection, stop
	Time bar	Support

All trademarks and registered trademarks are the property of their respective owners. GESS Technologies is a registered trademark of Global Engineering Security Systems.



<b>Video Detection &amp; Alarm</b>	Trigger Events	Recording, PTZ, Tour,Email
	Motion Detection	396 (22×18) detection zone, variable sensitivity levels
	Capture	JPEG capture
	Alarm Input	16ch.
	Alarm Output	4ch.NO,NC
<b>Playback &amp; Backup</b>	Max Playback	1/2/4/9/16 ch.
	Backup Mode	USB,HDD,Network Backup
<b>Network</b>	Ethernet	2 RJ-45 ports (10M/100/1000M)
	Network protocol	TCP/IP, UDP, HTTP, RTP/RTSP
	Network Functions	DHCP, PPPOE, DDNS,SMTP,SNTP,FTP,UPnP,P2P,3G
	Remote Operation	Monitoring,PTZ control,playback,system setting,file download,log information
	Smart Phone	iPhone,iPad,Android
<b>Hard Disk</b>	Hard Disk	8 SATA ports,each SATA supports 4TB
	E-SATA	1 E-SATA
	HDD Management	Hard disk hibernation technology, HDD faulty alarm&raid
<b>Auxiliary Interface</b>	USB Interface	2 USB 2.0 ports
	RS232	Support
	RS485	Standard 485, half duplex,PTZ control
<b>Environment</b>	Power Supply	110V~220V±10% 47-63Hz
	Power Consumption	20W (without HDD)
	Working Environment	0C~ + 55C / 10% – 90%RH
	Dimension(W*D*H)	2U, 440x450x90 (mm)
	Weight	7Kg (without HDD)
	Installation	Rack-mounted/Desktop type

\* These technical specifications are subject to change without prior notice. If you have any specific questions please contact us in advance of installation at 1.866.989.4082 extension #2 or ask for technical support.



**GESS®**  
TECHNOLOGIES

All trademarks and registered trademarks are the property of their respective owners. GESS Technologies is a registered trademark of Global Engineering Security Systems.

