



HD-SDI HIGH DEFINITION FIX FOCUS IR DOME CAMERA WITH WDR



KEY BENEFITS

- 1/3" Panasonic CMOS 16:9 full HD sensor
- IP65 weatherproof rating
- Advanced low light
- Smart noise reduction
- Fix focus 4mm lens
- Integrated lens separator
- No glare design
- OSD menu controls
- High Def 1080p over COAX

MODEL : ECL-HD40

SPECIFICATIONS

Designed with aesthetics in mind, the HD40 is produced for industrial applications where image adjusting is vital. The external / removable OSD joystick with test monitor output is ideal for demanding applications.

- Vandal resistant all metal
- Ball-in-socket design
- Highlight- Backlight compensation
- Advanced OSD menu
- Automatic gain control

The 3-dimensional mini-joystick on the video/power cable gives the user quick access to the OSD menu.



Move it left/right, up/down and "CLICK" to navigate the menu and make selections.

Video Sensor	1/3" Panasonic CMOS 16:9 Full HD sensor
Resolution	1920x1080P 2.1 Megapixel
Lens	Fixed 4mm lens
Illumination Range	0.5 LUX (0.0 LUX with IR on)
Video Output	SDI High Definition Output
White Balance	ATW (w/SET option), (OSD Control)
IR Range	100ft visual distance
IR LED Array	42 IR LEDS
Shutter	AES (OSD Control)
Gain Control	AGC (OSD Control)
Scanning System	Progressive Scan
Wide Dynamic Range	Yes, with Low/Middle/High & Off (OSD Control)
Dynamic Noise Reduction	2DNR, 3DNR, SMART DNR
Mechanical IR Filter	Mechanical Day/Night ICR-IR Cut Filter
BLC & HLC	Yes (OSD Control)
Image Control	Sharpness, brightness, color control (OSD Control)
Privacy	8 zone (OSD Control)
Day / Night	Adjustable (OSD Control)
Weatherproof Rating	IP65 (indoor/outdoor)
Vandal Resistance	Hardened case, cable feed-through
Power	12VDC 500mA (sold separately)
Housing	All metal (Ball-inSocket Design)
Dimension (inches)	4.2"(H) x 4.7"(W) (107mm x 120mm)
Weight	1.1 (lbs) 500(g)



ADVANCED TECHNOLOGY AT YOUR COMMAND

WWW.ECLIPSECCTV.COM